



WHAT DOLPHIN CUSTOMERS ARE SAYING

“THE BEST RAM TECHNOLOGY”

As VP of IC Engineering at Tiler Corporation and a customer of TSMC, I am submitting this testimonial for Dolphin Technology, an IP provider for TSMC. Tiler Corporation has used Dolphin Technology RAMs, ROMs, and I/Os across the 90nm, 40nm and 28nm nodes.

Tiler benchmarks consistently show that Dolphin has the best RAM technology, beating other top vendors in all dimensions – frequency, area and power. Dolphin's I/O IP incorporated important features starting in 90nm and below, technologies that other leading vendors have yet to implement in 28nm.

Dolphin understands that Tiler is a small company and provides flexibility and early access to technology. They support Tiler during design and well past first silicon, helping debug our issues, accepting feedback, and continuing to tune and improve their

offerings. For example, Dolphin kept Tiler informed and updated as they tuned IP to accommodate the 6 σ process variations seen in recent technologies. Dolphin fully embraces making their customers successful.

Dolphin has continued to expand their IP offerings to include extensive standard cell libraries, DfT tools and protocol controllers. The growth is planned and pertinent. Recently, they have instituted a customer tracking system that is increasing the quality of release mechanisms and product collateral.

Dolphin Technology has been an excellent partner for 8+ years.

John F. Brown III
Vice President, IC Engineering
Tiler Corporation

“A TRUSTED SUPPLIER AND PARTNER”

Since 2007, Sigma Designs has utilized Dolphin Technology's products in multiple projects across multiple process nodes. This includes Dolphin IP such as SRAM Memory Compilers (Single Port, Dual Port, 1-Port and 2-Port), Via ROM Memory Instances, Standard Cell Libraries (both High Density and High Speed) and DDR PHY Interfaces.

The first process node where Sigma used Dolphin IP was 90GP, and we have since used it in 55GP and 40LP as well. Dolphin has

repeatedly met our highest expectations about the quality of both the IP and the ongoing support we receive, and they have firmly established themselves as a trusted supplier and partner.

Jacques Martinella
Vice President, Engineering
Sigma Designs

“THE BEST DENSITY AND SPEED AT MINIMUM POWER”

We at GEO have used Dolphin Technology's IP in several products, and each time, we have been very pleased with the results.

In particular, we have found Dolphin's SRAM Compilers to provide the best density and speed at minimum power.

Their Standard Cell and I/O Libraries are also highly competitive in density, features, power and speed.

Sudhir Chandratreya
Vice President, Engineering
GEO Semiconductor

“USED IN MULTIPLE PROJECTS ACROSS MULTIPLE PROCESS NODES”

Juniper Networks has utilized Dolphin Technology's SRAM and standard cell products in multiple projects across multiple process nodes.

Dolphin has repeatedly met our expectations about the quality of both the IP and the ongoing support we receive, and over the years, they have established themselves as a trusted supplier and partner.

Bharat Bisen
Senior Director of Engineering

Juniper Networks

Front End views are available under NDA. For more information, contact [Dolphin Support](#) or sales@dolphin-ic.com

Dolphin Technology, Inc. 333 W Santa Clara Street, Suite 920 San Jose, CA 95113

www.dolphin-ic.com Tel: +1 (408) 392-0012 Fax: +1 (408) 392-0090



MEMORY COMPILERS

I/O

STANDARD CELLS

All IP's also available for 2/3/4/5nm/5nm+, 6nm, 7nm/7nm+, 12nm and 22nm

	16nm FF+ FFC	28nm HP, HPx LP, ULP	40nm G, LP ULP	55nm GP, LP ULP, EF	65nm GP LP	80nm G GC	90nm G, GT EF
STANDARD MEMORY & SPECIALTY MEMORY							
Single-Port & Dual-Port SRAM Compiler - Ultra Low Power / Ultra Low Leakage (RAMpiler [®])	● ¹	● ¹	● ¹	● ¹	● ¹	● ¹	● ¹
Single-Port & Dual-Port SRAM Compiler - High Performance and High Density (RAMpiler [®])	● ¹	● ¹	● ¹	● ¹	● ¹	● ¹	● ¹
Pseudo 2-Port Compiler - Higher Performance, Higher Density, Lower Power (RAMpiler [®])	● ¹	● ¹					
1-Port & 2-Port Register File Compiler - High Density and High Performance (RAMpiler [®])	●	●	●	●	●	2-Port (1R/1W)	2-Port (1R/1W)
Binary BCAM and Ternary TCAM Compiler (CAMpiler [®])	●	●	●	●	●	●	●
Via Programmable ROM and Diffusion ROM Compiler	●	●	●	●	●	●	●
Custom Register Files (4R/1W, 4R/2W, 3R/3W, 8R/1W, etc.)	● ^R	● ^R	● ^R	● ^R	● ^R	●	● ^R
Memory Test & Repair (BIST)	●	●	●	●	●	●	●

GENERAL PURPOSE I/O & SPECIALTY I/O

General Purpose I/O (GPIO)	●	●	●	●	●	●	●
I2C Interface	●	●	●	●	●	●	●
PVT compensated drive strength buffer	●	●	●	●	●	●	●
HSTL/SSTL Class I/II/III (DDR Combo)	●	●	●	●	●	●	●
DDR4/3/2 & LPDDR3/2 PHY Interface	●	●					
DDR3/2 & LPDDR2/1 PHY Interface			●	●	●	●	●
DLL for High Performance and Low Power products (digital)	67-1067 MHz	67-1067 MHz	67-1067 MHz	200-800 MHz	200-800 MHz		
LVPECL	● ^R	● ^R			●	●	●
LVDS drivers and receivers	● ^R	●	● ^R	●	●	●	●
LVDS/LVPECL combo pad	● ^R	● ^R	● ^R	● ^R	● ^R	●	●
Multi-Function I/O Interface (LVDS, DDR4/3/2, HSTL/SSTL, LVTTTL/LVCMOS, PCI 66/PCIX-133)	● ^R	● ^R	● ^R	●	●	●	
PCI-X 133 MHz and PCI-66/33 MHz						●	●
PCI-Express						●	●
HyperTransport [®] (HT-PHY)	● ^R	● ^R	● ^R	● ^R	● ^R	●	● ^R
Fibre Channel PHY, XAUI Ethernet Interface						● ^R	● ^R
SPI4.2 with Dynamic De-skew	● ^R	● ^R	● ^R	● ^R	● ^R		
Multi Function IO		●	●	●	●	●	●

STANDARD CELLS

Ultra High Density 6-track	●	● ²	●	●	●		
High Perf & High Density 7.5-track, Very HP 10.5-track	●						
Ultra Low Power & Ultra High Density 7-track		●	●	●	●	●	●
High Performance & Ultra High Density 9-track	●	●					
High Performance & High Density 10-track		●	●	●	●	●	●
Ultra High Performance & High Density 12-track	●	●	●				
Ultra High Performance 14-track		●					

¹ Without Redundancy ² 6.5-track for 28HPC ^R Upon Request

Front End views are available under NDA. For more information, contact Dolphin Support or sales@dolphin-ic.com

Dolphin Technology, Inc. 333 W Santa Clara Street, Suite 920 San Jose, CA 95113

www.dolphin-ic.com Tel: +1 (408) 392-0012 Fax: +1 (408) 392-0090



DDR PHY

DDR CONTROLLER

DDR DLL

	16nm FF+ FFC	28nm HP, HPx LP, ULP	40nm G, LP ULP	55nm GP, LP ULP, EF	65nm GP LP	80nm G GC	90nm G, GT EF
DDR PHY							
DDR4/3/2 PHY (DFI 4.0 compliant)	●	●	●	●	●		
LPDDR4/3/2 PHY (DFI 4.0 compliant)	●	●	●	●	●		
DDR3/2 PHY (DFI 4.0 compliant)			●	●	●		
Maximum speed, with 1.8V oxide (Mbps)	3200	3200	2133	1600	1600		
Maximum speed, with 2.5V oxide (Mbps)	1600	1600	1600	1600	1600		
IP is split into two hard macros (one for commands, control and address pins, one for 8-bit data bus)	●	●	●	●	●		
Supports custom number of address bits	●	●	●	●	●		
Compensation controller and pads for automatic driver and receiver termination impedance calibration	●	●	●	●	●		
Slew rate control, per-bit de-skew, gate training, read and write leveling	●	●	●	●	●		
JTAG signals for Mentor/Synopsys and LogicVision	●	●	●	●	●		
BIST with Pseudo Random Pattern Generator	●	●	●	●	●		
Scannable flops	●	●	●	●	●		
Wirebond, flip-chip and cup configurations	●	●	●	●	●		
Compliance to automotive quality standard, fault coverage 99.8%	●	●	●	●	●		

DDR CONTROLLER

DFI 4.0 Interface with Matching or 1:2, 1:4 Frequency Ratio	●	●	●	●	●	●	●
Built-in Gate Training and Read/Write Leveling	●	●	●	●	●	●	●
Maximum speed (Mbps)	3200	3200	2133	1600	1600	1600	1600
JEDEC Standard DDR5/4/3/2 and LPDDR5/4/3/2 SDRAM	●	●	●				
JEDEC Standard DDR3/2 and LPDDR2 SDRAM				●	●	●	●
Multi-port configurable AXI4 interface w/QoS signaling	●	●	●	●	●	●	●
Multi-port arbitration engine with programmable dynamic priority algorithm	●	●	●	●	●	●	●
Pipeline option for frequency vs. latency tradeoff	●	●	●	●	●	●	●
Fully configurable for various performances and requirements	●	●	●	●	●	●	●
FPGA portable (Xilinx PHY & Altera PHY compatible)	●	●	●	●	●	●	●
BFM verification suite	●	●	●	●	●	●	●
Single APB/AXI4-Lite programming interface	●	●	●	●	●	●	●
AXI4 dynamic QoS signaling for non-blocking communications	●	●	●	●	●	●	●
Support for low-latency bypass ports/channels	●	●	●	●	●	●	●
Advanced dynamic QoS support based on Queuing Theory and Traffic Hysteresis	●	●	●	●	●	●	●
Sideband and Inline ECC scheme	●	●	●	●	●	●	●

DDR DLL

DLL: High Precision DLL	●	●	●	●	●	●	●
DLL: Coarse and fine controls to minimize resolution errors	●	●	●	●	●	●	●
DLL: External bypass and check of generated delay code	●	●	●	●	●	●	●

Front End views are available under NDA. For more information, contact Dolphin Support or sales@dolphin-ic.com

Dolphin Technology, Inc. 333 W Santa Clara Street, Suite 920 San Jose, CA 95113

www.dolphin-ic.com Tel: +1 (408) 392-0012 Fax: +1 (408) 392-0090



eMMC/SD/SDIO I2C/I2S

eMMC/SD/SDIO – PHY & CONTROLLER	16nm FF+ FFC	28nm HP, HPx LP, ULP	40nm G, LP ULP	55nm GP, LP ULP, EF	65nm GP LP
Compliant with eMMC 5.1, SD 4.1 and SDIO 4.1 Specifications	●	●	●	●	●
Transfers data in HS400, HS200, DDR52, SDR52 compatibility modes	●	●	●	●	●
Supports HS400, HS200, DDR52 and SDR52 data transfer modes	●	●	●	●	●
Supports UHS-II (SD 4.0) data transfer rates up to 312MB/s	●	●	●	●	●
Supports UHS-I (SD 3.01) data transfer rates up to 104MB/s	●	●	●	●	●
Supports 32-bit and 64-bit system data bus and addressing	●	●	●	●	●
Tuning for HS200 mode	●	●	●	●	●
4KB block support	●	●	●	●	●
32 bit DMA interface	●	●	●	●	●
Interrupts and wake up functionality	●	●	●	●	●
Supports both Asynchronous and Synchronous AXI4 Interface	●	●	●	●	●
AXI4 Narrow Transfer	●	●	●	●	●
Enhanced strobe function for reliable operation at HS400 mode.	●	●	●	●	●
Host clock rate variable between 0 and 200 MHz	●	●	●	●	●
Transfers the data in 1-bit, 4-bit and 8-bit modes	●	●	●	●	●
Supports Low-Power mode	●	●	●	●	●
Supports CUP/Wirebond and Flip Chip configurations	●	●	●	●	●
Precision master/slave digital DLL is used for timing circuits.	●	●	●	●	●
PHY uses 6 metal layers. Higher metals are configurable for improved power and ground mesh	●	●	●	●	●
PHY includes built-in DLL (50-200 MHz) to handle high-speed operations	●	●	●	●	●
IDDQ Model	●	●	●	●	●
PVT compensation	●	●	●	●	●
Power supplies include Core VDD, I/O VDD and VSS	●	●	●	●	●
No use of deep n-well devices	●	●	●	●	●
Interrupts and wake up functionality	●	●	●	●	●

I2C/I2S - PHY & CONTROLLER

Drive programmable	●	●	●	●	●
Multi-mode support	●	●	●	●	●
Built in JTAG support for Mentor/LogicVision models	●	●	●	●	●
NAND or XOR tree select	●	●	●	●	●
Int/Out Register option	●	●	●	●	●
Pull down and sustain option	●	●	●	●	●
1.8 oxide	●	●	●	●	●
Metastability removal	●	●	●	●	●
Noise filter	●	●	●	●	●
Bus Start/Stop, stuck low detection	●	●	●	●	●
Signals (SDA/SCL) generation with user-defined timing constraints	●	●	●	●	●
Clock (SCL) synchronization	●	●	●	●	●
Bus arbitration	●	●	●	●	●
Customized I2C I/O:	●	●	●	●	●
• 1.8V / 2.5V oxide	●	●	●	●	●
• Multi-mode support	●	●	●	●	●
• Full power bus strapping based on metallization/top metal requirements (horizontal and vertical metallization option available from M6 and above)	●	●	●	●	●
• Available in Wirebond, Flip Chip and CUP configurations	●	●	●	●	●

Front End views are available under NDA. For more information, contact [Dolphin Support](mailto:sales@dolphin-ic.com) or sales@dolphin-ic.com

Dolphin Technology, Inc. 333 W Santa Clara Street, Suite 920 San Jose, CA 95113

www.dolphin-ic.com Tel: +1 (408) 392-0012 Fax: +1 (408) 392-0090



DolphinWare IPs

Libraries	ASIC	FPGA
Data Integrity	●	●
Control Logic	●	●
Logic Component	●	●
FIFO	●	●
FIFO Controller	●	●
Arithmetic Component	●	●
Verification IPs	●	●
Memory BIST	●	●
Watchdog Timer	●	●
Real-time Clock	●	●
Triple time Clock	●	●
PVT monitor	●	
Temperature monitor	●	
Digital DLL	●	●
Floating adder, multiply, divider, square root	●	●

Interfaces	ASIC	FPGA
JTAG Controller	●	●
UART/USART Controller	●	●
Serial Peripheral Interface Controller	●	●
Quad-Serial Peripheral Interface Controller	●	●
Octal- Serial Peripheral Interface Controller	●	●
Synchronous Serial Interface Controller	●	●
I3C Interface Controller	●	●
General-purpose Input/Output Controller	●	●
Pulse Width Modulator Controller	●	●
Interrupt Controller	●	●
Convert SPI to I2C interface	●	●
Convert SPI to UART interface	●	●
Convert APB to JTAG, JTAG to APB/AXI4	●	●
Encoder decoder AES, BCH, Reed Solomon	●	●
DMA controller	●	●
ONFI 5.0 controller	●	●
UHS PSRAM controller	●	●
UCle 1.1 controller	●	
PCIe 3.0 controller	●	
HBM 2e controller	●	



DOLPHIN Technology Partners & CUSTOMERS

PARTNERS

Dolphin Technology maintains cooperative partnerships with numerous industry leaders, enhancing the breadth and quality of our products and services.

These relationships enable us to offer value-added services to our customers, such as:

- Providing early access to test chip development
- Understanding customer roadmap requirements
- Providing early demand visibility
- Reducing time to market

Electronic Design Automation (EDA) Partners:

- Cadence
- Siemens EDA
- Synopsys

Design for Testability (DFT) Partners:

- LogicVision
- Siemens EDA
- Syntest

Memory Controller Partners:

- Northwest Logic



Ingenuity for life



SYNTEST
The Testability Company



NORTHWEST LOGIC
a Rambus Company

CUSTOMERS

Since 1996, Dolphin has worked with over 100 customers and completed hundreds of design projects. Our extensive, fab-verified offerings have met the most rigorous standards of the industry's most demanding companies.

Here are just a few of the industry-leading companies that trust and rely on Dolphin products:

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> • Broadcom • Cisco Systems • Ericsson • EZchip • Google • HiSilicon • Indie Semiconductor | <ul style="list-style-type: none"> • Intel • Juniper Networks • Lattice Semiconductor • LGE • Meta • Microchip | <ul style="list-style-type: none"> • Novatek • Onsemi • Qualcomm • STMicro • Texas Instruments • Toshiba • And many more |
|---|--|---|



Front End views are available under NDA. For more information, contact [Dolphin Support](#) or sales@dolphin-ic.com

Dolphin Technology, Inc. 333 W Santa Clara Street, Suite 920 San Jose, CA 95113

www.dolphin-ic.com Tel: +1 (408) 392-0012 Fax: +1 (408) 392-0090